



SANWAYAUDIO

<https://www.china-sanway.com>

DE250H-8

Specification

| | |
|-----------------------------------|-----------|
| Throat Diameter..... | 25mm |
| Nominal Impedance..... | 8ohms |
| Nominal Power Handling(1)..... | 40W |
| Continuous Power Handling(2)..... | 80W |
| Sensitivity(1M1W)(3)..... | 106dB |
| Frequency Range..... | 1-18KHZ |
| Voice Coli Diameter..... | 44mm |
| Winding Material..... | Aluminium |
| Former Material..... | Kapton |
| Fs..... | 900HZ |
| Recommended Crossover..... | 2 KHZ |
| Diaphragm Material..... | Polyimide |
| Flux Desity..... | 1.8T |



Mounting and Shipping Information

| | |
|-----------------------|--------------|
| Overall diameter..... | 120mm |
| Depth..... | 62mm |
| Net Weight..... | 2.1kg |
| Shipping Weight..... | 2.15kg |
| Shipping Box..... | 130*130*80mm |

(1) 2 hours test made with continuous pink noise signal(6dB crest factor) Power calculated on rated minimum impedance

(2) Power on Continuous Program is defined as 3 dB greater than the nominal rating

(3) Applied RMS Voltage is set to 2.83V for 8 Ohms Nominal Impedance

